



TREE PROTECTION DETAIL

NO SCALE

1. Chain link fence of a minimum 4-foot height shall be installed at or beyond the drip line. Poles shall be set in concrete block boots.
2. Poles shall be no further apart than 6' on center, 4 foot pole spacing is preferred.
3. Fencing shall not be installed closer to the tree than the drip line of those trees to be saved. Special circumstances shall be reviewed by the City.
4. Fencing shall be erected prior to any construction activity. The City shall be notified once the fencing is installed for inspection.
5. Under no circumstance shall the protective fencing be removed without proper approval from the City.
6. No person shall conduct any activity within the areas proposed to remain. This shall include, but not be limited to:
 - a. No solvents or chemicals within the protected areas.
 - b. No building materials or construction equipment within the protected areas.
 - c. No grade changes, including fill, within the protected areas.
 - d. No removal of vegetation from the ground up without permission from the City.
 - e. Any required swale needs to be directed around the protected areas. In instances where swales are approved through a protected area, the swales need to be HAND DUG. Machinery of any kind is prohibited.
7. Regulated Woodlands or Regulated Trees adjacent to the property are also required to be protected.
8. See Section 9.1000 Tree Regulations of the Gresham Community Development Code. Contact Gresham Planning Services at (503) 618-2842 with any questions.